K-LiTE lyra

"lyra" pendant and surface-mounted LED ceiling luminaires is the ideal choice for a variety of lighting applications. These fixtures feature high-quality LED sources that offer low energy consumption and an extended service life. Designed to perform at low mounting heights, these luminaires are perfectly suited for installation in a wide range of ceiling types-indoors and outdoors.

MATERIAL

Body : Aluminium Impact Protection : IK07 Ingress Protection : IP65

Diffuser : Clear Toughened glass Mounting : Surface / Pendant

ELECTRICAL

Driver : Standard Power Supply : Integral

Input Voltage : 230-240Vac / 50-60 Hz

Surge : 4KV

PRODUCT CONFIGURATIONS

Wattage : 30W LED (Upto 45W)

Beam Angle : 12° / 24° / 40°

CCT : 2700K / 3000K / 4000K / 5700K

LED Life Time : L70 B10 60,000 H

AREA OF APPLICATION

High Ceiling lobby, Retail outlets, Corridors, Corporate, Residential & Educational premises, Hospitality Industry, Commercial & Business Centers.

AVAILABLE FINISH

Pure polyester powder coated RAL 9004 Black RAL 9007 Grey aluminium

RAL 7016 Anthracite grey


RAL 9016 Traffic White

Graphite grey



K-LiTE lyra





Technical Specifications

General

ID

: 30W LED (Upto 45W) System Wattage Driver Integral : Constant Current Operating Voltage : 100-300Vac

Operating Temperature :-15°C~+50°C

Physical

Body : Aluminium Diffuser : Clear Toughened Glass Mounting : Surface / Pendant Finish : Powder coated

RAL 9004 Black

RAL 9007 Grey aluminium RAL 7016 Anthracite grey RAL 9016 Traffic White Graphite grey

Light Source

Light Source : NICHIA CRI (Ra) :≥80

LED Colour Temperature : 2700K / 3000K / 4000K

5700K

Driver

Power Supply : Integral Input Voltage : 230-240Vac Frequency : 50-60 Hz Power Factor :>0.95 :<10% Surge Protection : 4KV Efficiency :>85%

Optical Performance

Beam Angle : 12° / 24° / 40°

