



Technical Specifications

Light Source

Light Source	: LED
CRI (Ra)	: >90
LED Colour Temperature	: 2700K / 4000K RGBW / RGBW Pixel (Special colours on request)

General

Driver	: Constant Voltage
Operating Temperature	: -15°C~+50°C
Operating Voltage	: 24Vdc
Power Supply	: Non Integral 24V PSU (IP67)

Optical

Tilt	: Fixed
Beam Angle	: 120°
Diffuser Material	: Translucent Polyurethane Encapsulation

Physical

Body	: Extruded Aluminium with Stainless Steel Mounting Tray
Mounting	: Recess
Finish	: RAL9016 Traffic White / RAL9004 Black / Anodized Aluminium

Specification

Power (W/m)	10W/m	20W/m
Max.length (m)	2 mts	2 mts
Max.serial run length (m)	5 mts	3 mts
Max.ambient temp.(Ta _{max})	50°C	45°C

- The given data are standard values. Due to tolerances of the manufacturing process and the electrical components, photometric values and electrical power can vary up to 10 - 12%.
- Luminous flux upto -40% with opal transmission.
- In IP67 encapsulated products, tolerance in colour temperature can occur.
- Light distribution refer online



Ordering Guide

Recess

ID	Wattage	Dimension (mm)
23621	10W	515x 80 x 40
23621	20W	1015 x 80 x 40

Note : Luminaire operating voltage is 24Vdc, to be ordered with suitable power supply, controller and accessories.